



### Features

- Smoke detector and UFO outlook provides best concealment
- Minimum illumination: 0.04Lux
- High temperature resistant housing
- Len angle can be adjusted for ease of installment
- Screw-on design dome cover for easy and secured installation

### Specifications

Model	ADS-SDD-13480C	ADS-FSD-13480C
Outlook	Smoke Detector	Flying Saucer
Image Sensor	1/3" SONY Super HAD CCD	1/3" SONY Ex-view CCD
Effective Pixels	NTSC: 512(H)*492(V) PAL: 512(H)*582(V)(420TV)	
Scanning System	NTSC: 525 Lines; PAL: 625 Lines; 2:1 Interlace	
Signal System	PAL/NTSC	
Horizontal Resolution	480TVL	
Min Illumination	0.04Lux	0.05Lux
S/N Ratio	≥50dB	
Electronic Shutter	Auto 1/50(1/60)-1/100,000sec	
White Balance	Auto	
Backlight Compensation	Auto	
Auto Gain Control	Auto 自动	
Synchronization System	Internal	
Gamma Characteristic	0.45	
Video Output	1.0Vp-p 75Ω BNC	
Power Supply	DC 12V	
Operating Temperature	-10°C~ 50°C	
Storage Temperature	-20°C~ 65°C	
Lens	3.7mm/5.5mm	3.6mm



Smoke Detector Color Camera



Flying Saucer Color Camera



AES

AGC

ATW

BLC

DSP

S/N Ratio

Board Lens

Int Sync

Color-B/W