



Features

- Flame retardant PC Plastic dome cover
- Embedded Ceiling Mount
- Pattern Tours (path memory function)
- 4-Alarm input and 1-Alarm output
- Low illumination: Color Mode 0.4Lux; B/W Mode 0.01Lux
- Up to 255 speed domes can be supported on the RS-485 bus
- Built in Auto Focus / Auto Iris
- Automatically changed from Color to B/W mode
- 4 cruising tracks; each cruising track has 27 preset positions



Common Camera



Privacy Masking Feature

Specifications

Model	ADS-HID-14480Z230CB	ADS-HID-14480Z270CB
Image Sensor	1/4" Ex-view HAD CCD	1/4" Vertical double density interline CCD
Effective Pixels	NTSC: 768(H)*494(V) PAL: 752(H)*582(V)	
Scanning System	NTSC: 525 Lines; PAL: 625 Lines; 2:1 Interlace	
Signal System	PAL/NTSC	
Horizontal Resolution	480TVL	
Min Illumination	Color Mode:0.7Lux B/W Mode:1.0Lux	Color Mode:0.4Lux B/W Mode:0.01Lux
S/N Ratio	≥50dB	
Electronic Shutter	Auto 1/50(1/60)-1/100,000sec	
White Balance	Auto	
Backlight Compensation	On/Off	
Auto Gain Control	Auto/Manual	
Synchronization System	Internal	
Gamma Characteristic	0.45	
WDR	YES	NO
Pan Angle & Speed	0-360° , 0.05-180° /sec	
Tilt Angle & Speed	+2-(-90)° , 0.05-100° /sec	
Auto Flip	180°	
Preset Position	220	
Cruising Tracks	4	
Video Output	1.0±0.2Vp-p 75Ω BNC	
Power Supply	AC 24V	
Operating Temperature	0°C~ 50°C	-40°C~ 60°C
Storage Temperature	-20°C~ 60°C	
Len Focal Length	3.5~91mm	3.23~99mm
Zoom Ratio	23X Optical Zoom 10X Digital Zoom	27X Optical Zoom 10X Digital Zoom

