




Features

- G.726 Audio compression for Audio monitoring
- Built-in Web server for IE client support
- Support DDNS
- Support Motion detection and watermark
- Support Watchdog
- TCP/IP, ARP, RARP, ICMP, DHCP, FTP, HTTP, and SMTP protocol support
- Remote snap shot and video recording
- Self-contained FTP server & E-mail sending function
- Free multi-screen management software
- Support CDMA 1X and GPRS mobile network and surveillance via the mobile phone
- Support bi-directional real-time transmission of audio talk-back & broadcast
- Auto recovery for accidental network disconnection



Network Gun Camera



Network IR Hemisphere Camera

Specifications

Model	ADS-NG-13500C	ADS-NG-13520C	ADS-NID-13500CB	ADS-NID-13520CB
Camera Type	Network Gun Camera		Network IR Dome Camera	
IR Distance	NO		30m	
Image Sensor	1/3" SONY Super HAD CCD		1/3" SONY CCD	
Effective Pixels	NTSC: 704(H)*240(V) PAL: 704(H)*288(V) (500TV Lines)			
Scanning System	NTSC: 525 Lines; PAL: 625 Lines; 2:1 Interlace			
Signal System	PAL/NTSC			
Horizontal Resolution	500TVL	520TVL	500TVL	520TVL
Min Illumination	0.5Lux		Color Mode:0.3Lux B/W Mode:0.01Lux	
S/N Ratio	≥50dB			
Electronic Shutter	Auto 1/50(1/60)-1/100,000sec			
White Balance	Auto			
Backlight Compensation	On/Off			
Video Compression Format	H.264 baseline profile@Level2.2			
Video Input(Channels)	1			
Video Output(Channels)	1			
Display Frame Rate(fps)	PAL :1-25 NTSC:1-30			
Audio Input(Channels)	1			
Audio Output(Channels)	1			
Audio Compression Format	G.726			



AES



AGC



ATW



BLC



IR



WEB



S/N Ratio



Zoom Lens



Int Sync