




### Features

- Built-in infrared LED suitable for night surveillance
- Low light sensitivity
- Waterproof aluminium housing/bracket to IP 66 class, with sunshield
- IR LED radiant distance up to 40m/50m at night time (0 Lux)
- CDS auto switching IR LED control
- Built-in switching filter
- Automatically changed from Color to B/W mode

### Specifications

Model	ADS-WI-13500I40	ADS-WI-13480I50	ADS-WI-13520I50
IR Distance	40m	50m	
IR-LED	54pcs	104pcs	48pcs
IR Wavelength	850nm		
Image Sensor	1/3" SONY Super HAD CCD	1/3" SONY CCD	
Effective Pixels	NTSC: 768(H)*494(V) PAL: 752(H)*582(V)		
Scanning System	NTSC: 525 Lines; PAL: 625 Lines; 2:1 Interlace		
Signal System	PAL/NTSC		
Horizontal Resolution	500TVL	480TVL	520TVL
Min Illumination	0Lux (Less than 5Lux, IR-LED Auto on)		
S/N Ratio	≥50dB		
Electronic Shutter	Auto 1/50(1/60)-1/100,000sec		
White Balance	Auto		
Backlight Compensation	On/Off		
Auto Gain Control	Auto		
Synchronization System	Internal		
Gamma Characteristic	0.45		
Video Output	1.0Vp-p 75Ω BNC		
Power Supply	DC 12V ±5%	DC 12V ±10%	
Operating Temperature	-10°C ~ 55°C		
Storage Temperature	-20°C ~ 65°C		
Operating Environment	Indoor/Outdoor, Day & Night		
Lens(optional)	4~9mm	6/8mm	3.6/6/8/12mm



Common Camera



Color Waterproof IR Camera(Medium/Long Distance)

