



### Features

- Equipped with 2.4G locked frequency transmitter and receiver
- Minimum illumination: 0.01-1.0Lux
- Transmission distance: 50m/100m/500m
- Output of audio and video signal synchronously
- 2.5", 3.5" TFT LCD screen display as option
- The AA lithium batteries can work continuously for 2 hours after being refreshed
- Equipped with IR LED as option for night surveillance



Baby Monitor Wireless Camera



Home Monitor Wireless Camera

### Specifications

Model	ADS-WC-24420118T100	ADS-WC-63M380115T100	ADS-WC-63M380118T100
IR Distance	18m	15m	18m
Image Sensor	1/4" SHARP CCD	1/3" OMNIVISION CMOS	
Effective Pixels	NTSC: 510(H)*492(V) PAL: 628(H)*582(V)		
Scanning System	NTSC: 525 Lines; PAL: 625 Lines; 2:1 Interlace		
Signal System	PAL/NTSC		
Horizontal Resolution	420TVL	380TVL	
Min Illumination	0.01Lux	1.0Lux	
S/N Ratio	≥48dB		
Electronic Shutter	Auto 1/50(1/60)-1/100,000sec		
White Balance	Auto		
Backlight Compensation	On/Off		
Auto Gain Control	Auto		
Synchronization System	Internal		
Video Output	1.0Vp-p 75Ω BNC		
Transmission Distance	100m		
Frequency	CH1: 2.41 GHZ CH2: 2.432 GHZ CH3: 2.45 GHZ CH4: 2.468 GHZ		
Power Supply	DC 12V	DC 8V	DC 5V
Operating Temperature	-10°C~ 50°C		
Storage Temperature	-20°C~ 65°C		
Lens	3.7mm	3.6mm	3.6mm



AES



AGC



ATW



BLC



IR



DSP



S/N Ratio



Board Lens



Int Sync