



Board Lens



Features

- Single or double board available for selection
- Minimum illumination: 0.5-1.5Lux
- Low power consumption
- Audio board offered as option
- Automatically changed from Color to B/W mode

Specifications

Model	BL-SY3420FX ₃ C	BL-SP3420FX ₄ C	BL-SP4420FX ₅ C
Image Sensor	1/3" SONY CCD	1/3" SHARP CCD	1/4" SHARP CCD
Effective Pixels	NTSC: 510 (H) * 492 (V)		PAL : 500 (H) * 582 (V)
Scanning System	NTSC: 525 lines;	PAL: 625 lines;	2:1 Interlace
Signal System	PAL/NTSC		
Horizontal Resolution	420TV Lines		
Min Illumination	0.5Lux	1.5Lux	1.5Lux
S/N Ratio	>50dB		
Electronic Shutter	Auto 1/50(1/60)-1/100,000sec		
White Balance	Auto		
Synchronization System	Internal		
Video Output	1.0Vp-p 75 Ω BNC		
Power Supply	DC 12V 100mA		
Operating Temperature	-10°C ~ 50°C		
Storage Temperature	-20°C ~ 65°C		
Lens(optional)	3.6mm / 4mm / 6mm / 8mm / 12mm / 16mm		
Net Weight	150g		
Board Type	Double board		
Audio Board(optional)	Yes		

☆: X₃ = 036, 04, 06
 X₄ = 04, 06, 08, 12
 X₅ = 06, 08, 12, 16

