



Bullet Camera



Specifications

Model	BC-SP3420F037C	BC-SY3480F037C	BC-SY3520F036C
Image Sensor	1/3" SHARP CCD	1/3" SONY CCD	1/3" SONY CCD
Effective Pixels	NTSC: 510 (H) * 492 (V) PAL : 500 (H) * 582 (V)	NTSC: 768 (H) * 494 (V) PAL : 752 (H) * 582 (V)	NTSC: 811 (H) * 508 (V) PAL : 795 (H) * 596 (V)
Scanning System	NTSC: 525 lines;	PAL: 625 lines;	2:1 Interlace
Signal System	PAL/NTSC		
Horizontal Resolution	420TV Lines	480TV Lines	520TV Lines
Min Illumination	1.0Lux	0.5Lux	0.5Lux
S/N Ratio	>50dB		
Electronic Shutter	Auto 1/50 (1/60) - 1/100,000sec		
White Balance	Auto		
Backlight Compensation	On/Off		
Auto Gain Control	Auto		
Synchronization System	Internal		
Gamma Characteristic	0.45		
Video Output	1.0Vp-p 75 Ω BNC		
Power Supply	DC 12V 500mA		
Operating Temperature	-10°C ~ 50°C		
Storage Temperature	-20°C ~ 65°C		
Lens (optional)	3.7mm	3.7mm	3.6mm
Net Weight	150g		

Features

- High die cast aluminium construction
- Minimum illumination: 0.5-1.0Lux
- High signal to loss ratio with good picture quality
- Compact design providing best concealment and vandal proof
- Specially fit for prison, ATM and vehicle surveillance applications
- Automatically changed from Color to B/W mode

